

PA-5000 Series



Palo Alto Networks® PA-5000 Series of next-generation firewall appliances comprises the PA-5060, the PA-5050 and the PA-5020, all of which are targeted at high-speed data center and internet gateway deployments. The PA-5000 Series delivers up to 20 Gbps of throughput using dedicated processing and memory for the key functional areas of networking, security, threat prevention and management.

Key Security Features

Classifies all applications, on all ports, all the time

- Identifies the application, regardless of port, encryption (SSL or SSH), or evasive technique employed.
- Uses the application, not the port, as the basis for all of your safe enablement policy decisions: allow, deny, schedule, inspect and apply traffic-shaping.
- Categorizes unidentified applications for policy control, threat forensics or App-ID™ development.

Enforces security policies for any user, at any location

- Deploys consistent policies to local and remote users running on the Windows®, Mac® OS X®, Linux, Android®, or Apple® iOS platforms.
- Enables agentless integration with Microsoft® Active Directory® and Terminal Services, LDAP, Novell® eDirectory™ and Citrix®.
- Easily integrates your firewall policies with 802.1X wireless, proxies, NAC solutions, and any other source of user identity information.

Prevent known and unknown threats

- Blocks a range of known threats, including exploits, malware and spyware, across all ports, regardless of common threat-evasion tactics employed.
- Limits the unauthorized transfer of files and sensitive data, and safely enables non-work-related web surfing.
- Identifies unknown malware, analyzes it based on hundreds of malicious behaviors, and then automatically creates and delivers protection.



PA-5060



PA-5050



PA-5020

The controlling element of the PA-5000 Series is PAN-OS®, a security-specific operating system that natively classifies all traffic, inclusive of applications, threats and content, and then ties that traffic to the user, regardless of location or device type. The application, content and user – in other words, the business that run your business – are then used as the basis of your security policies, resulting in an improved security posture and a reduction in incident response time.

Performance and Capacities	PA-5060	PA-5050	PA-5020
Firewall throughput (App-ID enabled)	20 Gbps	10 Gbps	5 Gbps
Threat prevention throughput	10 Gbps	5 Gbps	2 Gbps
IPsec VPN throughput	4 Gbps	4 Gbps	2 Gbps
Max sessions	4,000,000	2,000,000	1,000,000
New sessions per second	120,000	120,000	120,000
Virtual systems (base/max ¹)	25/225	25/125	10/20

¹ Adding virtual systems to the base quantity requires a separately purchased license.

Networking Features

Interface Modes

- L2, L3, Tap, Virtual wire (transparent mode)

Routing

- OSPFv2/v3 with graceful restart, BGP with graceful restart, RIP, static routing
- Policy-based forwarding
- Point-to-Point Protocol over Ethernet (PPPoE)
- Multicast: PIM-SM, PIM-SSM, IGMP v1, v2, and v3
- Bidirectional Forwarding Detection (BFD)

IPv6

- L2, L3, Tap, Virtual Wire (transparent mode)
- Features: App-ID™, User-ID™, Content-ID™, WildFire®, and SSL decryption
- SLAAC

IPsec VPN

- Key exchange: Manual key, IKE v1 (pre-shared key, certificate-based authentication)
- Encryption: 3DES, AES (128-bit, 192-bit, 256-bit)
- Authentication: MD5, SHA-1, SHA-256, SHA-384, SHA-512

VLANs

- 802.1q VLAN tags per device/per interface: 4,094/4,094
- Aggregate interfaces (802.3ad) , LACP

Network Address Translation (NAT)

- NAT modes (IPv4): static IP, dynamic IP, dynamic IP and port (port address translation)
- NAT64, NPTv6
- Additional NAT features: Dynamic IP reservation, tunable dynamic IP and port oversubscription

High Availability

- Modes: Active/Active, Active/Passive
- Failure detection: Path monitoring, interface monitoring

Hardware Specifications

I/O

PA-5060 | PA-5050 - (12) 10/100/1000, (8) Gigabit SFP, (4) 10 Gigabit SFP+

PA-5020 - (12)10/100/1000, (8) Gigabit SFP

Management I/O

- (2) 10/100/1000 high availability, (1) 10/100/1000 out-of-band management, (1) RJ45 console port

Storage Options

- Single or dual solid state disk drives

Storage Capacity

- 120GB, 240GB SSD, RAID 1

Power Supply (Avg/Max Power Consumption)

PA-5060 - Redundant 450W AC (330W/415W)

PA-5050 | PA-5020 - Redundant 450W AC (270W/340W)

Max BTU/hr

PA-5060 - 1,416

PA-5050 | PA-5020 - 1,160

Input Voltage (Input Frequency)

- 100-240VAC (50-60Hz); -40 to -72 VDC

Max Current Consumption

- 8A@100VAC, 14A@48VDC

Max Inrush Current

- 80A@230VAC; 40A@120VAC; 40A@48VDC

Mean Time Between Failure (MTBF)

- 10.2 years

Rack Mountable (Dimensions)

- 2U, 19" standard rack (3.5"H x 21"D x 17.5"W)

Weight (stand-alone device/as shipped)

- 41 lbs/55 lbs

Safety

- cCSAus, CB

EMI

- FCC Class A, CE Class A, VCCI Class A

Certifications

See <https://www.paloaltonetworks.com/company/certifications.html>

Environment

- Operating temperature: 32 to 122 F, 0 to 50 C
- Non-operating temperature: -4 to 158 F, -20 to 70 C

To view additional information about the security features and associated capacities of the PA-5000 Series, please visit www.paloaltonetworks.com/products.



3000 Tannery Way
Santa Clara, CA 95054

Main: +1.408.753.4000

Sales: +1.866.320.4788

Support: +1.866.898.9087

www.paloaltonetworks.com

© 2017 Palo Alto Networks, Inc. Palo Alto Networks is a registered trademark of Palo Alto Networks. A list of our trademarks can be found at <https://www.paloaltonetworks.com/company/trademarks.html>. All other marks mentioned herein may be trademarks of their respective companies.
pan-ds-PA-5000-112917